

# SHENZHEN XINLIDAHONG TECH. CO., LTD.

## XLD-H SINGLE PANEL WALK THROUGH METAL DETECTOR



### Specification

<i>Display</i>	<i>LCD display</i>
<i>Boot self-check function</i>	<i>After booting, the system will automatically diagnose to confirm if the equipment running condition is normal or not. (2) System failure content will automatically display if there is a breakdown.</i>
<i>Operating system</i>	<i>Chinese/English menu option</i>
<i>Passing speed</i>	<i>The detection speed can be adjusted from the fastest 100 persons / minute(custom detection speed adjustment).</i>
<i>Background light time</i>	<i>0-99s. Display time can be continuous adjustable</i>
<i>Calendar</i>	<i>Display of year, month, day, minute.</i>
<i>Detection zones</i>	<i>5 detection zones</i>
<i>Alarm indication</i>	<i>(1) 1-25 s alarm time, 255 volumes can be adjusted continuously. (2) LED light alarming zone directly and accurately shows the location of prohibited body hidden item in corresponding height.</i>
<i>Sensitivity adjustment</i>	<i>(1) 255 sensitivity levels can be adjusted for homogeneous detection zones(three usage modes in different occasions.</i>

<i>Performance of anti-jamming</i>	<p>(1) Adopt temperature and humidity automatically detecting and tracking compensation technology, to adapt to different environments and climates to significantly improve the anti-interference ability.</p> <p>(2) Adjustable frequency, range from 4Khz to 8 Khz, to overcome outside interference by same frequency products.</p>
<i>Safety performance</i>	<p>(1) Adopt double protection passwords, only allow authorized personnel to operate, with higher security.</p> <p>(2) With factory setting restoring function in case of system errors caused by inadvertent operation by users.</p> <p>(3) Adopting uninterrupted power supply protection system, power battery lasts for 2-8 hours, the system has protection function for parameters (optional).</p> <p>(4) The power supply, at the bottom of the door, 12 v low voltage power supply, can be controlled by the operation panel, moisture-proof, waterproof and heat- dissipated.</p> <p>(5) Harmless to apparatus of cardiac pacing in human body, pregnant women, magnetic floppy disks, tapes, etc</p>
<i>Dry Contact</i>	<i>Able to work with access control systems</i>
<i>Tally function</i>	<i>Intelligent traffic counting and alarm functions, automatically statistics of the amount of pass and the number of alarms.</i>
<i>Operation place</i>	<i>Application: airports, places of entertainment, courts, etc.)</i>
<i>Power supply</i>	<i>Input AC85V ~ 264 v / 50-60 hz, adapter 12 v, power supply output current 3 a</i>
<i>Power</i>	<i>20 w, low power consumption, low radiation</i>
<i>Size</i>	<i>2000 mm (height) X400mm (width) X120mm (thickness</i>
<i>Detection distance</i>	<i>40-70cm</i>
<i>Weight</i>	<i>35kg</i>
<i>Operating environment</i>	<i>-20 °C- +45 °C</i>
<i>Standard</i>	<p>-With Inspection report by the Ministry of Public Security.</p> <p>-With registered trademark.</p> <p>-With appearance patent and utility model patent, no involve the use of intellectual property disputes.</p> <p>-Harmless to pregnant women and magnetic medium floppy disks, tapes, video, etc. conforming to "GB15210-2003".</p>